

Click to  
**ORDER**  
samples

AMES100-NZ



Enclosed

The AMES100-NZ is an AC/DC converter that offers much greater cost effectiveness due to material normalization and production automation also leading to improved reliability and performance. Offering a commercial input voltage range of 90-264VAC and an output voltage range from 5-48V, this series will offer many benefits to your new system design.

This new series offers great operating temperatures, from -30°C to 70°C also features an isolation of 4000VAC for improved reliability and system safety. Furthermore, a high MTBF of 600,000h, output short circuit protection (OSCP), output over-current protection (OCP) and an output over-voltage protection (OVP) come standard with the series.



The AMES100-NZ is suitable for street lighting controls, grid power, instrumentation, industrial controls, communication, and civil applications.

Features



- Universal Input: 90 - 264VAC/127 - 370VDC
- Operating Temp: -30 °C to +70 °C
- High isolation voltage: Up to 4000VAC
- Low ripple & noise, 200mV(p-p) typ.
- Output short circuit, over-current, over-voltage protection
- Regulated Output


Summary



Training



Product Training Video  
(click to open)



Application Notes

Applications



Power Grid



Industrial



Telecom



Instrumentation

## Models & Specifications

### Single Output

| Model           | Input Voltage (VAC/Hz) | Input Voltage (VDC) | Max Output Wattage (W) | Output Voltage (V) | Output Voltage Adjustable Range (V) | Output Current max (A) | Maximum capacitive load ( $\mu$ F) | Efficiency @230VAC Typ. (%) |
|-----------------|------------------------|---------------------|------------------------|--------------------|-------------------------------------|------------------------|------------------------------------|-----------------------------|
| AMES100-5SNZ-P  | 90-264/47-63           | 127-370             | 90                     | 5                  | 4.5-5.5                             | 18                     | 10000                              | 86                          |
| AMES100-12SNZ-P | 90-264/47-63           | 127-370             | 102                    | 12                 | 10.2-13.8                           | 8.5                    | 6800                               | 88                          |
| AMES100-15SNZ-P | 90-264/47-63           | 127-370             | 105                    | 15                 | 13.5-18                             | 7                      | 3300                               | 88                          |
| AMES100-24SNZ-P | 90-264/47-63           | 127-370             | 108                    | 24                 | 21.6-28.8                           | 4.5                    | 2200                               | 90                          |
| AMES100-36SNZ-P | 90-264/47-63           | 127-370             | 100.8                  | 36                 | 32.4-39.6                           | 2.8                    | 1000                               | 90                          |
| AMES100-48SNZ-P | 90-264/47-63           | 127-370             | 110.4                  | 48                 | 43.2-52.8                           | 2.3                    | 470                                | 91                          |

Note: The "-P" suffix indicates a terminal protective cover (ex. AMES100-5SNZ-P). For optional conformal coating, add "Q" after the "-P" (ex. AMES100-5SNZ-PQ is conformal coated version with terminal protective cover).

### Input Specifications

| Parameters      | Conditions         | Typical | Maximum | Units |
|-----------------|--------------------|---------|---------|-------|
| Input current   | 115VAC             | --      | 1.9     | A     |
|                 | 230VAC             | --      | 1.2     | A     |
| Inrush current  | cold start, 115VAC | 30      | --      | A     |
|                 | cold start, 230VAC | 50      | --      | A     |
| Leakage current | 240VAC             | --      | 0.75    | mA    |

### Output Specifications

| Parameters          | Conditions             | Typical   | Maximum | Units  |
|---------------------|------------------------|-----------|---------|--------|
| Voltage accuracy    | Full load, 5V output   | $\pm 2$   | --      | %      |
|                     | Full load, Others      | $\pm 1$   | --      | %      |
| Line regulation     | Full load              | $\pm 0.5$ | --      | %      |
| Load regulation     | 0-100% load, 5V output | $\pm 1$   | --      | %      |
|                     | 0-100% load, Others    | $\pm 0.5$ | --      | %      |
| Ripple & Noise*     | 5V output              | --        | 100     | mV p-p |
|                     | 12V, 15V output        | --        | 120     | mV p-p |
|                     | 24V output             | --        | 150     | mV p-p |
|                     | 36V, 48V output        | --        | 200     | mV p-p |
| Hold up time        | 115VAC                 | 10        | --      | ms     |
|                     | 230VAC                 | 55        | --      | ms     |
| Start-up delay time | Full load              | 500       | --      | ms     |

\* Ripple and Noise are measured at 20MHz bandwidth with a 47 $\mu$ F electrolytic capacitor and a 0.1 $\mu$ F ceramic capacitor. Please refer to the application note for specific details.



### Isolation Specifications

| Parameters                   | Conditions | Typical | Rated | Units      |
|------------------------------|------------|---------|-------|------------|
| Tested I/O voltage           | 60 sec     | --      | 4000  | VAC        |
| Tested Input to GND voltage  | 60 sec     | --      | 2000  | VAC        |
| Tested Output to GND voltage | 60 sec     | --      | 1250  | VAC        |
| Resistance (I/O, I/O to GND) | 500VDC     | --      | 100   | M $\Omega$ |



| General Specifications  |  |            |         |            |
|---|--|------------|---------|------------|
| Parameters  | Conditions   | Typical    | Maximum | Units      |
| Over voltage class  | Class III  |            |         |            |
| Switching Frequency   |  | 65         | --      | KHz        |
| Over Current protection   | Hiccup, Auto recovery                                      | ≥ 110      | 150     | % of Iout  |
| Over voltage protection*  | 5V output, shut down, Manual recovery                      | 5.7        | 6.7     | VDC        |
|   | 12V output, shut down, Manual recovery                     | 13.8       | 16.2    | VDC        |
|   | 15V output, shut down, Manual recovery                     | 18.7       | 21.7    | VDC        |
|   | 24V output, shut down, Manual recovery                     | 28.8       | 33.6    | VDC        |
|   | 36V output, shut down, Manual recovery                     | 41.4       | 48.6    | VDC        |
|   | 48V output, shut down, Manual recovery                     | 55.2       | 64.8    | VDC        |
| Short circuit protection  | Hiccup, Continuous, Auto recovery                          |            |         |            |
| Operating temperature   | See derating graph   | -30 to +70 | --      | °C         |
| Storage temperature   |  | -40 to +85 | --      | °C         |
| No-load power consumption   |  | --         | 0.5     | W          |
| Power derating  | 45 °C to 70 °C, 5V output                                  | 1.6        | --      | % / °C     |
|   | 50 °C to 70 °C, others                                     | 2          | --      | % / °C     |
|   | 90VAC - 100VAC   | 2          | --      | % / VAC    |
| Ambient temperature derating  | Operating altitude > 2000m                                 | 5          | --      | °C / 1000m |
| Temperature coefficient   | 0 °C to 50 °C  | ±0.03      | --      | % / °C     |
| Cooling   | Free air convection  |            |         |            |
| Humidity  | Non-condensing   | ≥ 10       | 95      | % RH       |
|   | Non-condensing, Operating                                  | ≥ 20       | 90      | % RH       |
| Vibration   | 10~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y,Z axes |            |         |            |
| Case material   | Metal  |            |         |            |
| Weight  |  | 340        | --      | g          |
| Dimensions (L x W x H)  | 5.08 x 3.82 x 1.18inch (129.0 x 97.0 x 30.0mm)             |            |         |            |
| MTBF  | > 600 000 hrs (MIL-HDBK -217F, t=+25°C)                    |            |         |            |
| NOTE: All specifications in this datasheet are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified. |  |            |         |            |

| Safety Specifications |   |   |
|-----------------------|---|---|
| Parameters            |   |   |
| Agency Approvals      | UL62368-1   |   |
| Standards             | Designed to meet EN/BS EN 61558, EN/BS EN 50178, EN/BS EN 60664-1, EN/BS EN 62477-1, over-voltage class III |   |
|                       | Information technology Equipment  | Designed to meet EN/BS EN 62368-1, EN/BS EN 61558-1, EN/BS EN 60335-1 |
|                       | EMC - Conducted and radiated emission   | CISPR32 / EN55032, class B  |
|                       | Harmonic current emission   | IEC/EN 61000-3-2, Class A   |
|                       | Voltage Changes, Voltage Fluctuation and Flicker  | EN 61000-3-3, Class A   |
|                       | Electrostatic Discharge Immunity  | IEC 61000-4-2 Criteria A  |
|                       | RF, Electromagnetic Field Immunity  | IEC 61000-4-3 Criteria A  |
|                       | Electrical Fast Transient/Burst Immunity  | IEC 61000-4-4 Criteria A  |
|                       | Surge Immunity  | IEC 61000-4-5 Criteria A  |
|                       | RF, Conducted Disturbance Immunity  | IEC 61000-4-6 Criteria A  |
|                       | Power-frequency Magnetic Field  | IEC 61000-4-8 Criteria A  |
|                       | Voltage dips, Short Interruptions Immunity  | IEC 61000-4-11 Criteria A   |

Derating



Dimensions



Note:  
Unit: mm(inch)  
Wire gauge: 22-12AWG  
Screw terminal tightening torque: M3.5, 0.58-m  
Mounting screw tightening torque: M3, 0.4N-m  
General tolerance: ±1.0(0.04)  
At least one of the ① - ⑨ location must be connected to PE

| Single Pin Output Specifications |                       |
|----------------------------------|-----------------------|
| Pin                              | Function              |
| 1                                | Input (L)             |
| 2                                | Input (N)             |
| 3                                | PE GND                |
| 4                                | -V Output             |
| 5                                | -V Output             |
| 6                                | +V Output             |
| 7                                | +V Output             |
| ADJ                              | Vout voltage adj knob |

**NOTE:** **1.** Datasheets are updated as needed and as such, specifications are subject to change without notice. Once printed or downloaded, datasheets are no longer controlled by Aimtec; refer to [www.aimtec.com](http://www.aimtec.com) for the most current product specifications. **2.** Product labels shown, including safety agency certifications on labels, may vary based on the date manufactured. **3.** Mechanical drawings and specifications are for reference only. **4.** All specifications are measured at an ambient temperature of 25°C, humidity<75%, nominal input voltage and at rated output load unless otherwise specified. **5.** Aimtec may not have conducted destructive testing or chemical analysis on all internal components and chemicals at the time of publishing this document. CAS numbers and other limited information are considered proprietary and may not be available for release. **6.** This product is not designed for use in critical life support systems, equipment used in hazardous environments, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet. **7.** Warranty is in accordance with Aimtec's standard Terms of Sale available at [www.aimtec.com](http://www.aimtec.com).